



Sicad s.p.A.

Via Caduti della Liberazione, 57
21040 Uboldo (VA) – Italia
Tel: +39 02 964121 Fax: +39 02 96412294
Web: www.eurocel.it

PRODUCT INFORMATION

EUROCEL EUROGRAPHIC 781/20

DESCRIPTION

Double coated tape for mounting printing plates in the flexographic process. With specially formulated adhesives no residues remain on plate or cylinder when tape is removed.

PRODUCT DATA

Carrier	PVC film; transparent
Adhesive	Natural rubber and resins
Liner	Ribbed PVC; brown

	Unit	Value	Method
Total thickness (without Liner)	mm	0.200	PSTC 133
Adhesion to steel	N/25mm	Int: 12.5 – Ext: 12.5	PSTC 101
Tensile strength	N/25mm	320	PSTC 131

APPLICATION

Mounting photopolymer or rubber plates on small diameter cylinders when high adhesion on plate & cylinder is preferred.

Features	Benefits	
Natural rubber based adhesive	<ul style="list-style-type: none"> ✓ High initial tack ✓ No edge lifting, even on small cylinders 	<ul style="list-style-type: none"> ✓ Clean and easy removal
PVC film	<ul style="list-style-type: none"> ✓ Controlled thickness consistency ✓ Ensures easy removal in one piece 	<ul style="list-style-type: none"> ✓ Provides high flexibility combined with high shear resistance
Ribbed PVC liner	<ul style="list-style-type: none"> ✓ Easy removal 	

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.