

3M™ 734 Abrasive Paper



Product Construction

<i>Mineral</i>	Silicon carbide
<i>Bonding</i>	Resin bond.
<i>Backing</i>	A – paper (P60 – P180) C – paper (P220 – P1200)
<i>Coating</i>	Closed
<i>Treatment</i>	Water resistance treatment
<i>Grit Range</i>	P80 – P1200
<i>Size</i>	230 mm x 280 mm

Available Forms



f

Applications

Materials:
Painted surface, synthetic and plastic materials

f

Recommendation

Recommended for roughing and finishing of fillers and primers, paint preparation and application of insulating

f

f

f

3M™ 734 Abrasive Paper

Features

Silicon carbide abrasives



Water resistance paper



Resin Bond



Advantages

Good cutting and finishing

Possible use in dry and wet conditions

Water resistance and delamination resistance



Benefits

Higher quality of worked surface

Higher time life and consistence cut

Higher time life

Machines



Safety



Quality

3M Plants are ISO 9002 certified.

Product Use: All statements, technical information and recommendations contained in this document are based on tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.



3M Italia SpA
Reperto ASD Abrasivi Industriali

Via Norberto Bobbio,21
20069 – Pioltello Milano
Tel: 02 7035 2529

Fax: 02 93660172

Data Sheet: 734

Issued 06/11

© 3M 2011. All rights reserved.