



Sicad s.p.A.

Via Caduti della Liberazione, 57
21040 Uboldo (VA) – Italia
Tel: +39 02 964121 Fax: +39 02 96412294
Web: www.eurocel.it

PRODUCT INFORMATION

EUROCEL ISOTAPE

DESCRIPTION

Single sided self-extinguishing PVC tape.

PRODUCT DATA

Backing	Soft PVC; several colours
Adhesive	Natural rubber and resins based

	Unit	Value	Method
Total thickness	mm	0.130	PSTC 133
Adhesion to steel	N/25mm	5	PSTC 101
Tensile strength MD	N/25mm	70	PSTC 131
Elongation at break	%	230	PSTC 131
Classification	IEC 60454-3-1-5/F-PVCP/90		

APPLICATION

Single sided insulating tape for electrical wiring and binding. Available in several colours.
According to CEI EN 60454-3-1.

Features	Benefits	
Natural rubber and resins based adhesive	✓ Highly sticky	✓ Well performing on several materials
Soft PVC backing	✓ Highly conformable ✓ Hand tearable	✓ Self-extinguishing

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.

VR003EN_REV02_ISOTAPE

Società Italiana Cellophane Adesivo
P.I. e C.F. IT 00220060123
Iscrizione R.E.A. Varese n. 129175
Reg. Imprese Varese n. 00220060123
Capitale Sociale € 15.000.000 i.v.