



20 Cocopan Crescent, Driehoek, Germiston
 Gauteng, South Africa
 Tel: +27 11 873 1311 FAX:+27 11 873 2396
 Web: www.eurocel.it

PRODUCT INFORMATION

EUROCEL TPL 201

DESCRIPTION

Single sided general purpose tape.

PRODUCT DATA

Backing	LDPE film laminated with cloth; available in several colours
Adhesive	Hot Melt Synthetic Rubber and Resins

	Unit	Average Value	Method
Total thickness	mm	0.180	PSTC 133
Adhesion to steel	N/25mm	14.0	PSTC 101
Tensile strength MD	N/25mm	85	PSTC 131
Elongation at break	%	15	PSTC 131
Temp. Resistance	°C	60°C	=

APPLICATION

General purpose single sided tape, suitable for binding of insulation covers such as pipes and panels, also fit for general packaging and “emergency” mending of sunshades, etc.

Features	Benefits	
Hot melt synthetic rubber and resin adhesive	✓ Good adhesion on irregular surfaces	✓ High performance on several materials
Laminated cloth LDPE backing	✓ High conformable ✓ Available in a wide range of colour	✓ Suitable for several kinds of applications ✓ Hand tearable

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; based on the product being stored at 15°C to 25°C with max. relative humidity of 65% out of direct sunlight. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature is lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad’s knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.

